

Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 NF 2706
- **Nitta Japan code:**



Construction: 2 plies polyester, non-rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Fabric	
Thickness:	0,6		-	mm (approx.)
Colour:	Nitta colour	Nitta colour	-	
Hardness:	85 Shore A		-	
Profile:	-		-	

Total thickness: 2,3 **mm (approx.)**
Weight: 2,9 **kg/m² (approx.)**
Max. width: 3000 **mm**
Belt support: Sliderbed (Rollers), Flat/trough

Rating at 1% elongation: 12 **N/mm**
Advised pretension: 4 - 7 **N/mm**
Maximum allowable tension: 22 **N/mm**
Temperature range: -10 **to** +80 **°C**

Minimum pulley diameters:
Flexing: 50 **mm**
Backflexing: 75 **mm**

Special approval: Not applicable

Applications: General purpose conveying
Curved conveyors and spiral conveyors